LED Panel Light （SKY TYPE）

LONGLUX



Dimmable
100% - 10%

Fire Resistant

LED Panel Light




Features

- Using solid state and free maintenance LED source,fast start and long life span.
- By design, paint optional.
- The shell adopts imported high density aluminum alloy material, has the strong collision and impact force of high.
- Beautiful appearance, light weight, convenient installation.
- Many different color temperature for customer to choose : warm white/nature white/cood white.
- A variety of installation for customers to choose.

Product Description



Product Dimension(mm)



Specification Sheet


Model	LLX-Panel-Blue sky-3D	LLX-Panel-Blue sky-2D
Voltage(V)	220-240	220-240
Power (W)	40	40
Lamp beads	4014	4014
LED QTY	192pcs	192pcs
CCT	bule-sky-3D	bule-sky-2D
P.F.	0.9	0.9
CRI	> 90	> 90
Dimensions(MM)	595*595*13	595*595*9

LED Panel Light


LONGLUX

Install Instructions


FRAME MOUNTED




SUSPENSION



RECESSED IN A CUT-OUT HOLE



CEILING MOUNTED



NOTES:

- ➤ Make sure the luminaries are installed and fitted by a qualified electrician ensuring the installation complies to the current.
- ➤ National Electrical Code and all local codes.
- ➤ Ensure all electrical connections are secure & that there are no loose strands.
- ➤ This is a Class I product and must be earthed.
- ➤ Make sure that the fixings are adequate to support the weight of the fitting.
- ➤ Before installation or maintenance, turn off electric power and allow the fitting to be cool.

WIRING INSTRUCTION OF MAIN CABLE:



black(or brown)line —— connect live wire
white(or blue)line —— connect neutral wire
green(or yellow-green)line —— connect earth wire

⚠ WARNING:

The product must be grounded and installed in accordance with the National Electrical Code and all local codes
Failure to do so may increase the RISH OF PERSONAL INJURY, PROPERTY DAMAGE, FIRE AND DEATH

LED Panel Light

LONGLUX

PACKAGING DATA



Model	LLX-Panel-Blue sky-3D	LLX-Panel-Blue sky-2D
QTY / CTN	5	5
Carton Dimensions(CM)	63.5*17.5*67	63.5*17.5*67
N.W.	14.5	14.5
G.W.	16	16

Applications:

Lighting for Supermarket, Family,Conference room,Warehouse,Office,Corridors and other places.







AFTER-SALE SERVICE

LONGLUX warrants this LONGLUX-branded hardware product against defects in materials and workmanship under normal use for a period of FIVE(5) YEARS from the date of purchase.LONGLUX provides free repair or replacement within warranty period.LONGLUX shall charge against defeats by abnormal storage,usage,connect on or change the structure or any components of the product.

*Damage by thunder stroke over 4KV(L,N to FG)/4KV(L to N) will not covered by warranty based on IEC6100-4-5.

ADD:
Hangzhou Longlux Electronic Technology Co. Ltd
TEL:+8613656681084
E-mail: william@longlux.com
Http: www.longlux.com