LED Batten Light

LONGLUX



Features

➤ Highlight LED lamp beads, with high brightness, uniform light emission, no dark areas or shadows, low light attenuation and good stability.

➤ Using a wide-voltage constant-current power supply, it has a wide application range, stable operation and a long service life.

➤ The PC face mask has uniform light distribution, high light transmittance, large light-emitting area, and is not prone to yellowing.

➤ Fully sealed lamp body, mosquito-proof, dust-proof and moisture-proof.

➤ Multiple profile options: Square, Oval, Slim and Grille designs to suit various installation requirements.

Certifications & Standards

CE IEC RoHS EMC CB DLC SAA GS

IP40 / IP65 available | IK08 Protection | 5 Year Warranty

Square Batten (transparent)



Model No.	Watt (W)	Voltage (V)	Color Temp.(K)	Lumens (Lm)	CRI (Ra)	Size (mm)
LLX-BPA-18	18W	85-265V	3000-10000K	1600	>70	600*65*24
LLX-BPA-36	36W	85-265V	3000-10000K	3000	>70	1200*65*24
LLX-BPA-50	50W	85-265V	3000-10000K	4000	>70	1200*65*24
LLX-BPA-70	70W	85-265V	3000-10000K	6000	>70	1200*75*24
LLX-BPA-100	100W	85-265V	3000-10000K	8000	>70	1200*100*24

Square Batten (milky white)



Model No.	Watt (W)	Voltage (V)	Color Temp.(K)	Lumens (Lm)	CRI (Ra)	Size (mm)
LLX-BPB-18	18W	85-265V	3000-10000K	1500	>70	600*65*24
LLX-BPB-36	36W	85-265V	3000-10000K	2900	>70	1200*65*24
LLX-BPB-50	50W	85-265V	3000-10000K	4000	>70	1200*65*24
LLX-BPB-70	70W	85-265V	3000-10000K	5800	>70	1200*75*24
LLX-BPB-100	100W	85-265V	3000-10000K	8000	>70	1200*100*24

Oval AL+PC Batten



Model No.	Watt (W)	Voltage (V)	Color Temp.(K)	Lumens (Lm)	CRI (Ra)	Size (mm)
LLX-BPC-18	18W	85-265V	3000-10000K	1500	>70	600*65*24
LLX-BPC-36	36W	85-265V	3000-10000K	2900	>70	1200*65*24
LLX-BPC-50	50W	85-265V	3000-10000K	4000	>70	1200*65*24
LLX-BPC-70	70W	85-265V	3000-10000K	5800	>70	1200*75*24

Oval AL+PS Batten



Model No.	Watt (W)	Voltage (V)	Color Temp.(K)	Lumens (Lm)	CRI (Ra)	Size (mm)
LLX-BPD-18	18W	85-265V	3000-10000K	1600	>70	600*65*24
LLX-BPD-36	36W	85-265V	3000-10000K	3000	>70	1200*65*24
LLX-BPD-50	50W	85-265V	3000-10000K	4250	>70	1200*65*24
LLX-BPD-70	70W	85-265V	3000-10000K	6000	>70	1200*75*24

Slim Batten



Model No.	Watt (W)	Voltage (V)	Color Temp.(K)	Lumens (Lm)	CRI (Ra)	Size (mm)
LLX-BPE-18	18W	85-265V	3000-10000K	1300	>70	600*70*24
LLX-BPE-36	36W	85-265V	3000-10000K	2800	>70	1200*70*24
LLX-BPE-70	70W	85-265V	3000-10000K	5200	>70	2400*70*24

Slim Plastic Batten



Model No.	Watt (W)	Voltage (V)	Color Temp.(K)	Lumens (Lm)	CRI (Ra)	Size (mm)
LLX-BPF-18	18W	85-265V	3000-10000K	1300	>70	600*76*23
LLX-BPF-36	36W	85-265V	3000-10000K	2800	>70	1200*76*23
LLX-BPF-45	45W	85-265V	3000-10000K	3500	>70	1500*76*23

Oval Plastic Batten



Model No.	Watt (W)	Voltage (V)	Color Temp.(K)	Lumens (Lm)	CRI (Ra)	Size (mm)
LLX-BPG-18	18W	85-265V	3000-10000K	1500	>80	600*62*28
LLX-BPG-36	36W	85-265V	3000-10000K	3000	>80	1200*62*28
LLX-BPG-45	45W	85-265V	3000-10000K	3800	>80	1500*62*28

Grille Batten



Model No.	Watt (W)	Voltage (V)	Color Temp.(K)	Lumens (Lm)	CRI (Ra)	Size (mm)
LLX-BPH-36	36W	85-265V	3000-10000K	3240	>80	1200*65*24
LLX-BPH-50	50W	85-265V	3000-10000K	4500	>80	1200*65*24
LLX-BPH-70	70W	85-265V	3000-10000K	6300	>80	1200*75*24
LLX-BPH-100	100W	85-265V	3000-10000K	9000	>80	1200*100*24

Applications

LED Batten lights are widely used in offices, warehouses, workshops, supermarkets, parking garages, corridors, schools, hospitals and other commercial and industrial applications. Available in various profiles and sizes to meet different lighting requirements.

AFTER-SALE SERVICE

LONGLUX warrants this LONGLUX-branded hardware product against defects in materials and workmanship under normal use for a period of **FIVE(5) YEARS** from the date of purchase. LONGLUX provides free repair or replacement within warranty period. LONGLUX shall charge against defects by abnormal storage, usage, connect on or change the structure or any components of the product.

*Damage by thunder stroke over 4KV(L,N to FG)/4KV(L to N) will not be covered by warranty based on IEC6100-4-5.

Contact

Hangzhou Longlux Electronic Technology Co., Ltd.

TEL: +86 136 5668 1084

E-mail: william@longlux.com

Web: www.longlux.com