Report No.: ETA16040100S-001

Test Report

Applicant	: Hangzhou Longlux Electronic Technology Co.,ltd
Address	: The Western Science Park, Hangzhou City, China
Sample Description	: Waterproof light
Brand Name/Trade Name	: Longlux
Model No.	: LLX-TriProof-118F; LLX-TriProof-218F; LLX-TriProof-236F; LLX-TriProof-236F; LLX-TriProof-158F; LLX-TriProof-258F; All modes are the similar construction except size and all the tests are to the type model LLX-TriProof-258F.
Rating	: 220-240V~; 50/60Hz; IP65
Factory	: Hangzhou Longlux Electronic Technology Co.,ltd
Address	: The Western Science Park, Hangzhou City, China
No. of Samples	: 1
Date of receipt of test item	: 2016-04-18
Date (s) of performance of test	: 2016-04-18 ~ 2016-04-22
Date of issue	: 2016-04-22
Service Requested	: IP65 Test
Method	: According to requirements of EN 60529:1991+A1:2000+A2:2013.
Result	: See the attached sheets.
Conclusion	:The testing of submitted sample **complied** with the above safety standards/requirement.

********** End of page **********

Prepared by:
ETA Testing Technology Co., Ltd

Zhou Yiping
Engineer
Luminaires Division

Reviewed by:
ETA Testing Technology Co., Ltd

Zha Lingzhi
Reviewer
Luminaires Division

- The results reported in this test report shall refer only to the sample actually checked and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reported except in full without prior authorization from ETA Testing Technology Co., Ltd.
- The services are provided subject to the terms and condition of the company, which can be furnished upon request.

Report No.: ETA16040100S-001

Test Item: IP65 Test Standard: EN 60529:1991+A1:2000+A2:2013

TEST CONDITION:

Ambient temperature: 25 °C

TEST METHOD:

1. Test for first characteristic numerals 6.

The specimen is tested in a dust chamber, in which talcum powder is maintained in suspension by an air current for a period of 3 hours. The chamber shall contain 2 kg of powder for every cubic meter of its volume.

2. Test for second characteristic numerals 5.

The specimen is switched off and immediately subjected to a water jet for 15 min from all directions by means of a hose having a nozzle with the shape. The nozzle shall be held 3m away from the sample. The water pressure at the nozzle shall be adjusted to achieve a water flow rate of 12.5l/min ± 5%.

TEST RESULT:

During IP6X test, the specimen was shown that no dust entry into internal part of the sample.

After IPX5 test, the specimen was shown that no water entry into internal part of the sample.

After completion of tests, the specimen was complied with requirements of the insulation resistance test and electric strength test.

These results comply with the standard Yes [√] No [ ]

EQUIPMENT USED:

ETA1051, ETA1052, ETA1104, ETA1144

Overview



Hangzhou ETA Testing Technology Co., Ltd.
8/F., Building A, The Western Science Park, Yuhang District, Hangzhou, Zhejiang, China
Telephone: +86-571-88610058; Fax: +86-571-88610058
Home Page: www.etatests.com