LED Panel Light (WIFI TYPE)

LONGLUX



Dimmable
100% - 10%

Fire Resistant


LED Panel Light



Features

- ➤Standard replacement for traditional grille light.
- ➤Ultra slim design,aluminum frame.
- ➤PMMA light guide plate,nice and consistent lighting distribution.
- ➤25000Hrs -50000Hrs lifespan.
- ➤Smooth and even light.

Product Details





Specification Sheet


Model No.	Voltage (V)	Power (W)	PF	LED CHIP	LUMENS (Lm)	C.T. (K)	CRI Ra	SDCM	Bean angle	Warranty	Driver
LLX- WiFi panel -CCT 40W	220VAC/240VAC 50-60Hz	40	≥ 0.9	SANAN 2835 SMD LED	IES 4000lm @4000K	CCT 3000-6500K	≥ 80	≤6	112°	2Y	GOLDMATCH
LLX- WiFi panel -CCT 48W	220VAC/240VAC 50-60Hz	48	≥ 0.9	SANAN 2835 SMD LED	IES 4000lm @4000K	CCT 3000-6500K	≥ 80	≤6	112°	2Y	GOLDMATCH
LLX- WiFi panel -RGB 40W	220VAC/240VAC 50-60Hz	40	≥ 0.9	SANAN 2835 SMD LED	IES 4000lm @4000K	RGB 3000-6500K	≥ 80	≤6	112°	2Y	GOLDMATCH
LLX- WiFi panel -RGB 48W	220VAC/240VAC 50-60Hz	48	≥ 0.9	SANAN 2835 SMD LED	IES 4000lm @4000K	RGB 3000-6500K	≥ 80	≤6	112°	2Y	GOLDMATCH

LED Panel Light


LONGLUX

Install Instructions


FRAME MOUNTED




SUSPENSION



RECESSED IN A CUT-OUT HOLE



CEILING MOUNTED



NOTES:

- ➤ Make sure the luminaries are installed and fitted by a qualified electrician ensuring the installation complies to the current.
- ➤ National Electrical Code and all local codes.
- ➤ Ensure all electrical connections are secure & that there are no loose strands.
- ➤ This is a Class I product and must be earthed.
- ➤ Make sure that the fixings are adequate to support the weight of the fitting.
- ➤ Before installation or maintenance, turn off electric power and allow the fitting to be cool.

WIRING INSTRUCTION OF MAIN CABLE:



⚠ WARNING:

The product must be grounded and installed in accordance with the National Electrical Code and all local codes
Failure to do so may increase the RISH OF PERSONAL INJURY, PROPERTY DAMAGE, FIRE AND DEATH

LED Panel Light

PACKAGING DATA



Model No.	LGP thickness (mm)	Diffuser (mm)	Reflect Sheet (mm)	Back Cover (mm)	SIZE (mm)
LLX- WiFi panel -CCT 40W	PMMA2.3	PS 1.0	PET0.225	0.28	595*595*9
LLX- WiFi panel -CCT 48W	PMMA2.3	PS 1.0	PET0.225	0.28	295*1195*9
LLX- WiFi panel -RGB 40W	PMMA3.0	PS 1.0	PET0.225	0.28	595*595*9
LLX- WiFi panel -RGB 48W	PMMA3.0	PS 1.0	PET0.225	0.28	295*1195*9

Applications:

Lighting for Supermarket, Family,Conference room,Warehouse,Office,Corridors and other places.







AFTER-SALE SERVICE

LONGLUX warrants this LONGLUX-branded hardware product against defects in materials and workmanship under normal use for a period of FIVE(5) YEARS from the date of purchase.LONGLUX provides free repair or replacement within warranty period.LONGLUX shall charge against defeats by abnormal storage,usage,connect on or change the structure or any components of the product.

*Damage by thunder stroke over 4KV(L,N to FG)/4KV(L to N) will not covered by warranty based on IEC6100-4-5.

ADD:
Hangzhou Longlux Electronic Technology Co. Ltd
TEL:+8613656681084
E-mail: william@longlux.com
Http: www.longlux.com